

AI Basics — S01E06: Agentic Workflows, Tool Calling, Model Context Protocol (MCP) & Production Guardrails

A rigorous architectural guide for backend and AI engineers.



Gemini Notebook

"Autonomy is an engineering discipline, not a model capability."



This reference architecture replaces high-level theory with actionable engineering patterns, protocol-level mechanics, and production-grade security models.

Gemini Notebook


Architectural Distinction: Workflows vs. Agents

	Code-Driven Workflows	Model-Driven Autonomous Agents
Control Flow	**Deterministic.** Orchestrated through predefined code paths.	**Non-deterministic.** Model dynamically directs its own processes and tool usage.
State Management	Handled by the host application's memory/variables.	Handled by the model's ongoing context window and self-reflection loops.
Predictability	**High cost/latency predictability.** Optimal for well-defined subtasks.	**Low cost/latency predictability.** Required for open-ended problems requiring environmental feedback.

Gemini Notebook


Code-Driven Workflows: Sequential & Parallel Topologies

Prompt Chaining




Trades latency for accuracy by decomposing tasks into fixed subtasks.

Routing



Separates concerns based on intent classification (e.g., routing simple queries to smaller, cheaper models).

Parallelization




Handles multiple considerations simultaneously; highly effective for guardrail sectioning or vulnerability voting.

Gemini Notebook

Code–Driven Workflows: Dynamic Topologies

`{ while (condition_met) { ... ... ... } }`

Orchestrator-Workers



Best for complex tasks where the number of subtasks cannot be predicted upfront (e.g., refactoring an unknown number of files).


Evaluator-Optimizer



Best when evaluation criteria are clear and iterative refinement provides measurable value (e.g., translation, test-driven code generation).

Gemini Notebook

The Math of Autonomy: Compounding Error Rates




Why we default to workflows: Compounding multi-step error math.

Autonomous agents trade cost and latency **predictability** for **flexibility**. Only deploy full autonomy when the required path cannot be pre-computed. Multi-step autonomy requires **near-perfect single-step reliability** to yield a successful end state.

Gemini Notebook

ReAct Loop Architecture: Synergizing reasoning and acting




Interleaving reasoning traces (**Thought**) with actions (**Action**) prevents hallucination and grounds the model's subsequent decisions in actual environmental state rather than predicted continuation.

Gemini Notebook

The Execution Trust Boundary

The LLM never executes code oo directly.




The model merely predicts grammar-constrained JSON matching a provided schema. The host runtime bears sole responsibility for parsing the string, validating types, authorizing the action, and executing the native function.

Gemini Notebook

ACI Design: Poka-Yoke Tool Engineering

HCI (Human-Computer Interface)



Poka-yoke: Mistake-proofing. Designing interfaces where it is structurally impossible for the model to make common errors.

ACI (Agent-Computer Interface)

```
{
  "tools": [
    {
      "name": "search_tool",
      "description": "Searches for information regarding a query.",
      "parameters": {
        "type": "object",
        "properties": {
          "query": {
            "type": "string",
            "description": "The search query string."
          }
        },
        "required": ["query"]
      }
    }
  ],
  "Poka-yoke: Mistake-proofing. Designing interfaces where it is
  structurally impossible for the model to make common errors."
}
```

Investing in rigorous API design and tool parameters heavily outperforms attempting to fix bad tool usage via overall prompt tweaking.

Gemini Notebook

Schema Design Best Practices

```
{
  "location": { "type": "string" },
  "path": { "type": "string" },
  "description": "Gets weather"
}
```

Free-text location field

Relative file paths

Vague description


```
{
  "location": {
    "type": "string",
    "description": "City name or lat/lon."
  },
  "units": {
    "type": "string",
    "enum": ["metric", "imperial", "kelvin"]
  },
  "description": "Get current weather. Must use absolute paths. Defaults to metric if units omitted."
}
```

- enum constraints strictly limit the model's output space, preventing hallucinated parameters.
- Explicit edge-case handling in the docstring acts as a micro-prompt, guiding the model precisely at the moment of tool selection.

Gemini Notebook


The M x N Integration Matrix Problem

Before: The M x N Problem



The M x N Integration Matrix: Without standardization, AI applications must build custom integrations for every tool.


After: The M + N Solution



The MCP Standard: MCP standardizes context exchange, completely decoupling the AI host application from the underlying data/tool server implementation.

Gemini Notebook


MCP Network Topology: Host, Client, Server



A local or remote program that provides context, tools, and prompts to the client.

Gemini Notebook

JSON-RPC 2.0 Lifecycle & Transports



Protocol

Stateless exchange utilizing JSON-RPC 2.0. Each request carries protocol version and capabilities in its `_meta` field.

Transport Layers

- Stdio: Direct local process communication. Zero network overhead.
- Streamable HTTP/SSE: Remote server communication supporting standard HTTP authentication (OAuth/Bearer tokens).

Gemini Notebook


The Three Core MCP Primitives

The three core building blocks servers use to provide context to AI applications, separated by locus of control.

Tools (Action)	**Resources** (Data)	**Prompts** (Templates)
`tools/list`, `tools/call`	`resources/list`, `resources/read`	`prompts/list`, `prompts/get`
Executable functions (e.g., Search flights, run SQL).	Passive data URIs (e.g., `file:///path`, `db://schema`).	Reusable instruction templates templates with parameters.
Model-controlled.	**Application-controlled.**	**User-controlled.**
The LLM actively decides when/how to use them based on prompts.	The host app retrieves and attaches this to the context window.	Explicitly invoked by the human (e.g., slash commands).

Gemini Notebook


Context Management & Dynamic Discovery



Mitigating context-window bloat by avoiding upfront loading of hundreds of schemas. MCP supports lazy loading and progressive tool discovery via opt-in, long-lived subscription streams, ensuring the LLM only sees tools relevant to the current system state.

Gemini Notebook


The Agentic Threat Landscape



- When models cross the threshold from processing data to acting on environments, the threat model upgrades exponentially.
- Failures mutate from “bad text output” on a screen to “unintended system mutation” in a production database.

Gemini Notebook

Indirect Prompt Injection (The Lethal Trifecta)




The attacker never interacts with the agent directly. The malicious payload is planted in external content the agent is expected to process. Because the agent cannot distinguish between legitimate tool output and injected instructions within that output, it executes the attacker's payload using its own trusted credentials.

Gemini Notebook


Confused Deputy & State Corruption

Confused Deputy (Privilege Escalation)



Inter-agent trust escalation where permissions are improperly inherited across agent boundaries.


State Corruption (Persistent Memory Poisoning)



When an agent writes a hallucination or injected payload into persistent memory, permanently poisoning its future reasoning context. (Also risks infinite retry loops burning compute).

Gemini Notebook

The Execution Environment Security Boundary




Do not rely on model behavior for security.
A model falling for a prompt injection `inside` a `tightly` sandboxed environment produces a completely different outcome than one with `unrestricted egress`.

Hard boundaries (sandboxing, strict egress rules, ephemeral credentials) are the only reliable way to contain the blast radius of an agentic compromise.

Gemini Notebook


Human-in-the-Loop (HITL) & Approval Policies

Bad Pattern: Per-Action Approval



Per-action approval for multi-step agents habituates users to clicking ‘yes’, degrading the security control.

Good Pattern: Plan Review



Force the agent to surface a read-only plan. Let the human review the intent before the agent is authorized to execute the batch. Use MCP metadata to flag specifically irreversible/destructive actions for hard stops.

Gemini Notebook


Trajectory Evaluations & Observability

Single-Turn Eval



[Insufficient]

Trajectory Eval




[Required]

Agent evaluations must measure the entire execution trajectory, not just the final text output. Key Metrics: Tool selection accuracy, parameter formatting precision, recovery from API errors, and adherence to negative constraints over long horizons.

Gemini Notebook

Architectural Graduation Checklist



Final Takeaway: Start simple. Only upgrade to full autonomy when the rigidity of a workflow demonstrably fails the use case. Autonomy is expensive; spend it wisely.

Gemini Notebook