
# Web Architecture — S02E00

## Life of a Production Request: End-to-End Infrastructure Map

> A millisecond-by-millisecond autopsy of scale, latency, and distributed systems.





Gemini Notebook

# The Monolithic Ceiling

A single server inevitably collapses under scale. Vertical scaling is bounded by hard physical constraints.



### Compute Exhaustion

Thread pools saturate, leading to total CPU starvation and missed RPC deadlines.

### Memory Pressure

High in-flight request volume increases RAM usage, triggering the Java "GC Death Spiral" (garbage collection consumes all remaining CPU).

### Resource Limits

Operating systems run out of Process IDs and File Descriptors (FDs), outright rejecting new network connections.

Gemini Notebook

# The Geographic Speed-of-Light Penalty

**You cannot out-engineer physics.**

$$\frac{\text{Distance}}{\text{Speed of Light in Fiber}} = \text{Absolute Minimum RTT}$$





- A client in Paris connecting to a single server in Los Angeles faces an inescapable Round Trip Time (RTT) penalty. penalty.
- TCP handshakes and TLS 1.3 cryptographic negotiations require multiple round trips before a single byte of HTTP data is sent.
- Geographic distance translates directly to latency degradation.

Gemini Notebook

# Containing the Blast Radius

Redundancy alters probability. True resilience requires isolating systems into discrete failure domains (Regions, Availability Zones, and Cells) to prevent correlated failures.





```
PROBABILITY(Node A Fail) = 0.01%
PROBABILITY(Node A + Node B Independent Fail) = 0.000001%
WARNING: Shared infrastructure bypasses mathematical redundancy.
```

Gemini Notebook

# The DNS Resolution Funnel

Before the HTTP request begins, the human-readable domain must resolve to an IP address.

DNS caching short-circuits this lookup, saving hundreds of milliseconds at the edge.





**SHORT CIRCUIT: CACHE HIT**

Governed by TTL (Time To Live)

**Bypasses Root, TLD, and Authoritative servers entirely.**

Gemini Notebook

# BGP Anycast & Edge Termination



## BGP Anycast Routing

Routes volumetric traffic to the topologically closest edge server sharing the exact same IP address.

## TLS 1.3 Termination

Cryptographic handshakes are handled at the geographic edge, slashing Round Trip Time (RTT) penalties before touching the cloud.

## RFC 9111 CDN Caching


Static assets are served directly from the PoP memory.

Prevents volumetric traffic from ever traversing the ocean to hit the cloud origin.

Gemini Notebook

# L7 Web Application Firewall (WAF)


The edge absorbs malicious volumetric and targeted traffic before it impacts origin compute budgets.




1. Negative Security (Blocklist): Drops known attack signatures instantly.
2. Positive Security (Allowlist): Admits strictly pre-approved traffic profiles.
3. Rate Limiting: Absorbs HTTP floods and Layer 7 enumeration bots.

Gemini Notebook

# Entering the Cloud Region: L4 Distribution




## Virtual IPs (VIPs)

- VIPs hide the backend fleet. The L4 Load Balancer intercepts the VIP traffic and selects a physical backend.
- GRE Encapsulation tunnels the packet to the backend, avoiding Layer 2 broadcast domain limitations.

## Consistent Hashing

- Maps packets to backends using a deterministic algorithm to minimize connection resets when a backend node fails or scales.

```
id(packet) mod N
```

Gemini Notebook

# The Ingress Disambiguation Matrix

| Technology | OSI Layer | Statefulness | Protocol Awareness | Latency Cost |
|---|---|---|---|---|
| CDN | Layer 7 | Stateless (Cache) | HTTP/HTTPS | <20ms (Hit) |
| L4 NLB | Layer 4 | Connection State | TCP/UDP | ~1ms |
| L7 ALB / Reverse Proxy | Layer 7 | Request State | HTTP/gRPC | ~3-5ms |
| API Gateway | Layer 7+ | Auth/Rate-Limit State | REST/GraphQL | ~10-20ms |

Gemini Notebook

# Compute Isolation Fleet

Modern infrastructure decouples horizontal compute elasticity from durable state. Linux primitives enforce strict hardware-to-software abstraction.

### Linux Namespaces

Provides strict process and networzk isolation. To the application, it appears as a completely independent OS environment.

### Linux cgroups (Control Groups)


Strictly enforces CPU and memory resource limits. Prevents noisy neighbor starvation and out-of-memory cascading panics.




Gemini Notebook

# The Anatomy of a Cascading Failure

A cascading failure is driven by positive feedback loops. Without circuit breakers, a single localized resource exhaustion event inevitably causes total systemic collapse.




Gemini Notebook

# The Retry Storm Amplifier

Naive retries destabilize systems. If a backend rejects requests due to overload, immediate front-end retries dwarf the original load, creating a self-inflicted DDoS attack.

- Fewer requests succeed, but backend resources are completely consumed just parsing the doomed retries.
- The retries themselves mathematically guarantee the backend remains in an overloaded state.





Gemini Notebook

# Exponential Backoff & Jitter

*If at first you don't succeed, back off exponentially.*


Adding mathematical randomness (jitter) to retry intervals is mandatory. Without jitter, a network blip causes all clients to retry at the exact same millisecond, crushing the recovering backend.




Gemini Notebook

# Load Shedding & RPC Deadlines

When overloaded, servers must fail early and cheaply. Spending resources on requests that will ultimately exceed their client deadlines is wasted compute (**Bimodal Latency**).





## Deadline Propagation

Passing **absolute timeouts** down the **stack** ensures that if a frontend gives up after **5 seconds**, the deep **database query** is aborted instantly. Doomed work is purged from the queue before it consumes **CPU**.

Gemini Notebook

# Workload Isolation: Shuffle Sharding

If all servers process identical traffic pools, a “Query of Death” kills the entire fleet simultaneously. Shuffle Sharding mathematically contains catastrophic failure to a fractional shard.




Gemini Notebook


# The Caching Topology Matrix

| Topology | Architecture Type | Coherence | Failure State | Primary Feature |
| --- | --- | --- | --- | --- |
| Inline Cache | Read-Through (e.g., HTTP Proxy) | High | Dependency appears down | Uniform API model; transparent to app |
| Side Cache | Cache-Aside (e.g., Application checked) | Requires manual invalidation | Graceful degradation to DB possible | App orchestrates cache checks directly |
| Local Cache | In-Memory (e.g., Guava) | Low (Fleet drift risk) | Cold start penalty on reboot | Ultrafast; zero network overhead |
| External Cache | Dedicated Fleet (e.g., Redis) | Consistent fleet-wide state | Introduces own failure domain | Scales independently from compute |

Gemini Notebook

# Surviving the Thundering Herd

A “Cold Cache” causes a sudden, catastrophic surge of simultaneous traffic to the unprotected persistence layer. Soft TTLs and Coalescing act as vital shock absorbers.




**Request Coalescing**

The system recognizes identical simultaneous requests, holds 999 in an asynchronous queue, sends exactly 1 query to the database, and serves the single result to all 1,000 clients.


**Soft vs Hard TTLs**

Serving slightly stale data (Soft TTL) from memory is infinitely preferable to browning out the downstream database (Hard TTL) during a cache rebuild.

Gemini Notebook

# The Persistence Layer: Async Queues & Databases

Databases are the hardest layer to scale horizontally. Bursty state mutations must be decoupled to protect primary durability.




- Connection pooling and multiplexing are mathematically required to prevent database thread exhaustion.
- Read required to prevent database thread exhaustion.
- Read-heavy workloads are offloaded to asynchronously synchronized Read-Replicas, trading strict consistency for total availability.

Gemini Notebook

# The End-to-End Latency Ledger

**Architecture is the practice of managing latency and blast radius.**

| PATH A: CACHE HIT | |
|---|---|
| DNS Resolution | + 2ms |
| Edge TLS Handshake | + 15ms |
| Edge Cache Hit | + 1ms |
| TOTAL LATENCY BUDGET | = 18ms |


Resolved at the network edge.
Never touches cloud compute.

| PATH B: STATE MUTATION | |
|---|---|
| DNS Resolution | + 2ms |
| Edge TLS Handshake | + 15ms |
| Region Transit (Fiber) | + 40ms |
| L4/L7 Routing | + 5ms |
| Compute Processing | + 40ms |
| DB Commit | + 60ms |
| Return Transit | + 43ms |
| TOTAL LATENCY BUDGET | = 205ms |

Traverses all 7 OSI layers.
Carries highest blast radius risk.

Gemini Notebook

# Series Roadmap: S02 Masterclass




Gemini Notebook